

Specifications of DD-104LCD-FA2

LCD Display	Lcd Size		10.4 inch(Diagonal)				
	Display Resolution (Dot)		800X3(RGB)X600 support display up to 1920×1080 format				
	Active area		211.2(H) x 158.4(V)				
	Dot pitch		0.264(W)X0.264(H) mm				
	Aspect Ratio		4:3				
	Brightness		250 CD/M ²				
	Contrast Ratio		500:1				
	Light Source		LED				
	Surface treatment		Anti-Glare				
	Response Time Note 1		Symbol	Condition	Min	Typical	Max
		Rise	Tr		-	5 ms	10 ms
		Fall	Tf		-	15 ms	20 ms
	View Angle		70/70(Left/Right) and 50/65 (Up/Down)				
Video Input Signal	Analog RGB						
Touch Screen	4 wire touch screen, USB or RS232 interface						
Compatibility	PC						
	MAC						
Inputs	1 VGA input, 2 RCA Video Inputs, 1 RCA Audio Input						
Input Connector	15-pin D-sub, RCA A/V input, DC plug						
Power	AC adapter to DC		Input: 100-240V, 50/60Hz, 0.60A Output: 12V, 1200 am				
	DC : 12V, 1200 am						
Power Consumption	< 10 Watts						
Control	Basic		Power, Auto Adjustment, Source, Brightness up/down, 4 Levels Brightness by one button, OSD Menu				
	Advance		Adjust Brightness, Contrast, Saturation, Tint, Sharpness, Phase, Clock, Color Temperature, H position, V position, OSD Language				
Speaker	Built in, 1 Watts						
Remote Control	Infrared remote Control						
Stand	Built-in						
Menu Language	English/French/Russian/German/Chinese						
Cabinet Color	Black						
Storage temperature	(-20)°C -(+ 70°)C						

Specifications of DD-104LCD-FA2

Operation Temperature	$(-10)^{\circ}\text{C} - (+60)^{\circ}\text{C}$	
Operation at High Temperature and Humidity	$(+50)^{\circ}\text{C}$, 80% RH Max	
Product Dimension (without Stand)	252L \times 216W \times 73H(Folding)	
Package Contents	Monitor, Power adpter, 15-pin D-sub Cable, Remote Control, Driver CD	

Note 1: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.

