

Specifications of DD-104LCD-FA6

| | | | | | | |
|------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------------|-------------|
| LCD Display | Lcd Size | 10.4 inch(Diagonal) | | | | |
| | Display Resolution (Dot) | 800X3(RGB)X600 support display up to 1920×1080 format | | | | |
| | Active area | 211.2(W)X158.4(H) mm | | | | |
| | Dot pitch | 0.264(W)X0.264(H) mm | | | | |
| | Aspect Ratio | 4:3 | | | | |
| | Brightness | 250 CD/M ² | | | | |
| | Contrast Ratio | 500:1 | | | | |
| | Light Source | LED | | | | |
| | Surface treatment | 3H | | | | |
| | Response Time Note1 | Sym bol | Condition | Min (ms) | Typical (ms) | Max (ms) |
| | Tr | 25°C | - | 5 | 10 | |
| | Tf | | - | 15 | 20 | |
| | View Angle (Degree) | 70/70(Left/Right) and 50/60 (Up/Down) | | | | |
| Video Input Signal | Analog RGB | | | | | |
| Compatibility | PC | | | | | |
| | MAC | | | | | |
| Inputs | 1 VGA, 1 HDMI, 1 DVI, 1 S-Video, 1 Component, 2 composite input and 1 Audio Input, 1 Audio out put | | | | | |
| Touch Screen | Four wire resistive touch screen | | | | | |
| Touch screen interface | USB (RS232 optional) | | | | | |
| Input Connector | VGA, HDMI, DVI, S-Video, Component, RCA input | | | | | |
| Power | AC adapter to DC | | Input: 100-240V, 50/60Hz, 0.60A Output: 12V, 1200 am | | | |
| | DC : 12V, 1200 am | | | | | |
| Power Consumption | < 10 Watts | | | | | |
| Control | Basic | | Power, Auto Adjustment, Source, Brightness up/down, 4 Levels Brightness by one button, OSD Menu | | | |
| | Advance | | Adjust Brightness, Contrast, Saturation, Tint, Sharpness, Phase, Clock, Color Temperature, H position, V position, OSD Language | | | |
| Speaker | Built in, 1 Watts | | | | | |
| Remote Control | Infrared remote Control | | | | | |
| Stand | Built-in | | | | | |
| Menu Language | English/French/Russian/German/ Chinese | | | | | |
| Cabinet Color | Black | | | | | |
| Storage temperature | (-10)°C -(+ 70°)C | | | | | |

Specifications of DD-104LCD-FA6

| | | |
|--------------------------------------------|----------------------------------------------------------------------|--|
| Operation Temperature | (0)°C –(+ 50°)C | |
| Operation at High Temperature and Humidity | (+ 50°)C, 80% RH Max | |
| Product Dimension (mm) | 260L × 200W × 40H | |
| Package Contents | Monitor, Power adpter, 15-pin D-sub Cable, Remote Control, Driver CD | |

Note 1: Definition of Response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.

