3U 16-Bay Storage Server Rackmount Chassis



Features

- Fiber Optical Drive Tray Status Indicator
- Advance Thermal Cooling Design Optimizes Airflow
- 4 Hot-swappable 80mm Cooling Fans with Status Monitor
- Support EATX Motherboard
- miniSAS (SFF-8087) HDD Backplane
- Front Access USB Connector
- Power + Fan Failure + HDD LED Indicator
- · Power/Alarm Reset Switch
- Fully RoHS Compliance
- Support 6.0Gb/s SAS/SATA Hard Drives

Specifications

Model Number		Expansion Slots
E3M16		7
RoHS Compliance		Material of Handle
YES		Aluminum
Form factor		Material of Main Chassis
3 U		Heavy-duty SGCC Cold-rolled Steel
Standard Drive Bays		Motherboard Size
2.5" Drive (internal): 1	Slim 3.5" FDD: 1	12 x 13 (EATX, ATX, microATX)
Hotswap 3.5": 16	Slim 5.25" Optical: 1	
Hotswap HDD Type:		Cooling Fan
3.5" SAS I/II & SATA I/II/III	l	2x60mm, 4x80mm
Indicators		Dimensions (WxHxD)
Power + Fan Failure + HD	D LED	Width 19.00" (482.6 mm) Height 5.25" (133.3 mm) Depth 27.00" (685.8 mm)
Switches		2000 (00000 11111)

Power On/Off, Reset, Mute

Front View



Inside View




Rear View



We at iStarUSA Group offer OEM/ODM services for Industrial Power, Custom Power, Chassis, Cabinets, and Data Storage. Through our skilled metal bending, milling, and silk screening we can provide you with unique customizations that will make your product stand out from the rest. With iStarUSA Group's OEM/ODM Solutions you can be sure to receive one-of-a-kind products for your one-of-a-kind business.





Ordering Information

Model	Description	
E3M16	3U 16-Bay Storage Server Rackmount Chassis	

Compatible Power

PSU Model	Description
IS-2U35PD8	IS 2U 80PLUS 350W
IS-2U46PD8	IS 2U 80PLUS 460W
IX-1300R2UPD8	2U 1300W 80+ Platinum Redundant
IX-1600R2UPD8	2U 1600W 80+ Platinum Redundant
IX-750S2UPD8G	2U 750W 80+ Gold Redundant

Optional Accessories

Category	Model
Sliding Rail Kit	TC-RAIL Series Sliding Rail Kit