



REF. D.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	LENGTH		
P1 24	1	+3.3V	ORANGE	20	JW C4202H02 -A20P+ C4202H02 -A4P+ OR EQUIV	200±15 mm		
	2	+3.3V	ORANGE	20				
	3	COM	BLACK	20				
	4	+5V	RED	20				
	5	COM	BLACK	20				
	6	+5V	RED	20				
	7	COM	BLACK	20				
	8	PW-OK	GRAY	24				
	9	+5Vsb	PURPLE	20				
	10	+12V	YELLOW	20				
	11	+12V	YELLOW	20				
	12	+3.3V	ORANGE	20				
	13	+3.3V	ORANGE	20				
	14	+3.3VS	BROWN	24				
	15	-12V	BLUE	24				
	16	COM	BLACK	20				
	17	PS-ON	GREEN	24				
	18	COM	BLACK	20				
	19	COM	BLACK	20				
	20							
	21	+5V	RED	20				
	22	+5V	RED	20				
	23	+5V	RED	20				
	24	COM	BLACK	20				
PA	1	+12V	YELLOW	20	AMP 1-480424-0 or EQUIV.	250±15 mm		
	2	COM	BLACK	20				
	3	COM	BLACK	20				
	4	+5V	RED	20				
PC	1	+12V	YELLOW	20	AMP 1-480424-0 or EQUIV.	310±15 mm		
	2	COM	BLACK	20				
	3	COM	BLACK	20				
	4	+5V	RED	20				
PB	1	+12V	YELLOW	20	AMP 171822-4 or EQUIV.	150±10 mm		
	2	COM	BLACK	20				
	3	COM	BLACK	20				
	4	+5V	RED	20				
PD	1	+12V	YELLOW	20	AMP 1-480424-0 or EQUIV.	150±10 mm		
	2	COM	BLACK	20				
	3	COM	BLACK	20				
	4	+5V	RED	20				
PE	1	COM	BLACK	20	MOLEX 39-01- 2040 or EQUIV.	310±15 mm		
	2	COM	BLACK	20				
	3	+12V	YELLOW	20				
	4	+12V	YELLOW	20				
PF	1	+12V	YELLOW	20	CI1271H80 -15P or EQUIV.	310±15 mm		
	2	COM	BLACK	20				
	3	+5V	RED	20				
	4	COM	BLACK	20				
	5	+3.3V	ORANGE	20				
PG	1	+12V	YELLOW	20	CI1270H00 -15P or EQUIV.	150±10 mm		
	2	COM	BLACK	20				
	3	+5V	RED	20				
	4	COM	BLACK	20				
	5	+3.3V	ORANGE	20				

NOTE:

1. ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.
2. 產地標籤依業務指示加貼.
3. PE+12V請插PCB+12V1孔，其餘插+12V2孔

UNIT:mm



MODEL NO. :	TC-1U15FX1	TITLE: ASSY	SHEET: 1 OF 1 REV:01
R&D(2)	PE	DRAWN	DATE
		樂家龍	Jul.17.2008
INTERIOR COUNTERSIGN:			